






TECHNICAL DETAILS

Item Code	X502	
Composition	75% PL - 25% CO	
Colours		PISA - CAT. B
Width	55 inch	
Fabric Weight per Metre	800 gr/ml	
Colour shades may slightly vary from dye-lot to dye-lot		
TEST		RESULT
RESISTANCE TO ABRASION - Martindale Method UNI EN ISO 12947-2/2000		> 100.000 rubs
COLOUR FASTNESS WET AND DRY RUBBING (FRICTION) -Method UNI EN ISO 105 X 12:2016		Dry: 4/5 Wet: 4
TENSILE STRENGHT - Method EN ISO 13934-1		Warp: 2800 N Weft: 560 N
COLOUR FASTNESS TO ARTIFICIAL LIGHT - Method UNI EN ISO 105 B02: 2014		4/5
SEAM SLIPPAGE - Method 13936-2		Warp: 5 mm. Weft: 6 mm.
PILLING - Method EN ISO 12945-2		4
FR		TB 117:2013 California
<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Wash at or below 30 °C</p> </div> <div style="text-align: center;">  <p>Do not tumble dry</p> </div> <div style="text-align: center;">  <p>Dry clean</p> </div> <div style="text-align: center;">  <p>Iron low heat</p> </div> <div style="text-align: center;">  <p>Do not bleach</p> </div> </div>		