

TECHNICAL DETAILS

| | | |
|-------------------------|--|--------------------------|
| Item Code | M200 | SORRENTO - CAT. D |
| Composition | 93% PP Recycled - 7% PL | |
| | IN-OUT-DOOR RECYCLED | |
| | WATER REPELLENT - ANTIMICROBIAL | |
| Width | 55 inch | |
| Fabric Weight per Metre | 650 gr/ml | |

COLOUR SHADES MAY SLIGHTLY VARY FROM DYE-LOT TO DYE-LOT

| TEST | RESULT |
|------|--------|
|------|--------|

| | |
|--|-------------|
| RESISTANCE TO ABRASION - Martindale Method UNI EN ISO 12947-2/2000 | 30.000 rubs |
|--|-------------|

| | |
|--|----------------------|
| COLOUR FASTNESS WET AND DRY RUBBING (FRICTION) -Method UNI EN ISO 105 X 12:2003 | Dry: 4/5 Wet: 4/5 |
|--|----------------------|

| | |
|--|---|
| COLOUR FASTNESS TO ARTIFICIAL LIGHT - Method UNI EN ISO 105 B02/04 - A1 (March 2002) | 7 |
|--|---|

| | |
|--|----------------------|
| DIMENSIONAL CHANGE TO WASHING 30° C - Method UNI EN ISO 6330 | Warp: 1% Weft: 1% |
|--|----------------------|

| | |
|---|-----|
| PILLING - Method EN ISO 12945-2 | 4/5 |
|---|-----|

| | |
|-----|---|
| FR: | BS 5852 Part 1 Source 0 (Cigarette Test) TB 117:2013 California NFPA 260/UFAC EN1021-1 |
|-----|---|

