

## TECHNICAL DESCRIPTION

<b>Item</b>	<b>VULCANO - CAT. A</b>		
<b>Composition</b>	100% PL		
<b>Minimum Guaranteed Width</b>	55	[inch]	
<b>Weight</b>	530±5%	[g/m]	
<b>Approximate Roll Length</b>	45-50	[m]	
<b>Finishing</b>	WATER REPELLENT		
<b>Abrasion Resistance Test EN ISO 12947-2 (Martindale)</b>	>40.000	[giri]	
<b>Pilling Test ISO 12945-2: 2020 (Martindale)</b>			
	<b>Pilling</b>	4	[grado/grade]
	<b>Fuzzing</b>	4	[grado/grade]
	<b>Matting</b>	4	[grado/grade]
<b>Colour Fastness to Rubbing ISO 105 X 12</b>	<b>Dry</b>	4	[grado]
	<b>Wet</b>	3	[grado]
<b>Colour solidity to artificial light Xenotest ISO 105 - B02</b>		4	[grado]
<b>Flame resistance CAL TB 117:2013</b>	PASS		
<b>Dimension Fastness to Washing 30°C</b>	<b>Weft</b>	max 2	%
	<b>Warp</b>	max 2	%
<b>Washing Instruction and Care</b>			
<p>Wash at or below 30 °C    Do not bleach    Iron low heat    Dry clean    Do not tumble dry</p>			